



Cactus® Double Coated Film Tape

Technical Data Sheet No. Y2560

Product Information

Cactus® Double Coated Film Tape Y2560 is an acrylic solvent-based pressure sensitive adhesive that offers exceptional shear strength and a high peel adhesion level, providing quick bonding results. Ideal for permanent bonding to most substrates such as metal, wood, glass, cement and plastics.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 8.3 mil (0.21 ± 0.01mm)
Carrier	: 2 mil UPVC film	Loop Tack	: FINAT-9 105.6 oz/inch (3 kg/25mm)
Liner Thickness	: 3.0 mil	Tack	: J Dow No. 14
Liner Material	: Glassine Paper	Peel Adhesion	: PSTC-1 88 oz/inch (2.5 kg/ 25 mm)
Liner Density	: #60 (90 g/m ²)	Shear Strength PSTC-7	: Over 72 hrs with 35.2 oz loading on 1' x 1" (1.0 kg / 25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Color	: Mustard	Heat Resistance	: Over 24 hrs with 17.6 oz loading on 1' x 1" (0.5 kg / 25mm x 25mm) bonding 2 stainless steel plates at 176°F (80°C)
Tape Color	: White	Service Temperature	: -22°F ~ 194°F (-30°C ~ 90°C)
Tensile Strength	: MD:15.40 lbs/in (7.0 kg/mm ²); TD: 9.9 lbs/in (4.50 kg/mm ²)	Elongation	: MD: 150% TD: 120%

Applications

- Permanent bonding to most substrates, such as metal, wood, glass, cement & plastics
- For mounting decorative trims such as PVC profile for for the Furniture Industry
- Fastening of nameplates, trophy, luggage tag, wooden trims, signs etc.

Storage and Shelf Life

For best results, store this product at 72°F (22°C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.

