Cactus® Double-Coated Paper Tape

Technical Data Sheet No. M265S

Product Information

Cactus® Double-Coated Platemounting Tape M265S is a 15 mil cloth tape with rubber pressure sensitive adhesive, ideal for off-set printing, and solid, line and combination printing. This model offers high performance adhesive system that bonds the plate to the cylinder firmly and enables clean removal after use.

Composition & Physical Properties				
Adhesive System : Th	nermosetting Rubber SA	Tape Thickness	:	15 mil (0.39 ± 0.02 mm)
Liner Thickness : 3.5	5 mil	Tack	:	J. Dow No. 16
Carrier Material : Co	otton cloth, 105 g/m²	Peel Adhesion PSTC-3	:	42.32 oz/inch (1.2kg / 25mm)
Liner Material : Gla	lassine Paper	Shear Strength PSTC-7	:	Over 24hrs with 2.21 lbs loading on 1" x 1" (1.0kg / 25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Density : #6	60 (90 g/m²)	Service Temperature	:	14°F ~ 140°F (-10°C ~ 60°C)
Liner Color : Mu	ustard	Tape Color	:	Beige

Applications

- Main applications: Temporary mounting of blanket printing plates for offset printing machine.
- Also suitable for fixing nameplates, plastic injected stripes and carpets, etc.

Storage and Shelf Life

For best results, store this product at 72°F (22°C) and 50% relative humidity, use within 2 years from date of receipt.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.